

ABURA MP GREASE

PRODUCT DESCRIPTION

- Available in NLGI grade 000, 00, 0, 1, 2, 3
- Multipurpose lithium soap thickened and mineral oil based greases

APPLICATIONS

- Wide ranges of industrial applications that do not require heavy load carry capacity, high temperature and specified lubrication capacity.
- Wheel bearing of motorcycle.
- Mild to medium-duty applications found in manufacturing facilities, automobiles, agricultural and construction equipment.
- NLGI Grade of 000~0 are suitable for use in centralized lubrication system for pump car and light duty vehicles

BENEFITS

- Good mechanical stability supported by stable lithium soap thickener
- Versatile application to various types of roller bearings, sliding bearing, centralized lubrication system for normal conditions.
- Reduces friction and wear under mild loads

TECHNICAL SPECIFICATION

Test Items	Unit	Test Method	NLGI			
			0	1	2	3
Thickener	-	-	Lithium Soap			
Appearance	-	Visual	Smooth Dark Brown			
Worked Penetration (25°C, 60 strokes)	0.1mm	ASTM D 217	355-385	310-340	265-295	220-250
Dropping Point	°C	ASTM D2265	Min.180			
Copper Corrosion	-	ASTM D4048	Max. 1b			
Oil Separation	Wt%	ASTM D 6184	-		Max. 2.0	