

ABURA LICOM EP MOLY 3%

PRODUCT DESCRIPTION

- Available in NLGI Grade 0, 1, 2, 3
- Lithium complex soap and highly refined mineral oil based greases
- For use in temperature that general lithium grease cannot stand
- Contain unleaded EP additive, inhibitors for oxidation, rust and corrosion
- Lithium complex thickener provides high dropping point and stability

APPLICATIONS

- Wheel bearing of passenger car, bus, truck, farm, construction equipment and other commercial vehicles
- Lubrication of loaded slide, ball and various shock loaded or vibrating parts in transport, agriculture and off-load vehicles.
- Recommended temperature range : -20°C - 160°C

BENEFITS

- Good resistance to heat to avoid excessive softening or hardening
- High wear protection and oxidation stability
- Good protection against rust, corrosion and water washout
- Excellent for automotive application

TECHNICAL SPECIFICATION

Items	Unit	Test Method	NLGI			
			0	1	2	3
Thickener	-	-	Lithium Complex Soap			
Appearance	-	Visual	Smooth Red, Blue, Green, Natural			
Worked Penetration (25°C, 60 strokes)	0.1 mm	ASTM D 217	355-385	310-340	265-295	220-250
Water Washout	Wt%	ASTM D 1264	-		Max. 2.0	
Oil Separation	Wt%	ASTM D 6184	-		Max. 2.0	
Dropping Point	°C	ASTM D 2265	-	Min. 285		
Copper Corrosion	-	ASTM D 4048	Max. 1b			
4-Ball EP Test	kgf	ASTM D 2596	Min. 400			
Welding Point	mm	ASTM D 2266	Max. 0.6			